

PREADD AS 534

0611

PREADD AS 534 is an antistatic masterbatch with a polypropylene carrier developed for cast-PP and BOPP films.

PREADD AS 534 is based on a combination of fast and slow migrating additives. Like all migrating antistatic additives PREADD AS 534 may affect the printing, heat sealing and bonding properties of the film.

The addition level of PREADD AS 534 should be tested in advance for the desired antistatic effect with the polymer used.

PREADD AS 534 is approved for use in contact with foodstuffs according to FDA regulations as long as the dosage level of PREADD AS 534 is less than 1.6 % and according to BgVV regulations as long as the dosage level is less than 2.5 %.

Appearance	Granule
Carrier	PP homo polymer
Colour	Transparent
Additive	Slow and fast migrating antistatic additives, 10 %
Density	0.9 g/cm ³
Temperature stability	< 260 °C
Dosing	0.5 – 2.5 %
Moisture content	Max. 0.25% when produced
Packaging	1000 kg in 20 kg PE valve bags on a one-way stretch wrapped pallet, or 1000 kg in octabins
Storage	Can be stored for one year in its original package. Packages should be stored indoors.

The information in this data sheet represents typical values obtained by us and should not be regarded as a specification.

We condition that the product will be inspected and qualified by the customer for his process to meet the specific requirements set by application, processing equipment and end product.